

TRANSIT

Transit — The People Mover

The Transit Bus and Kombi range of vehicles. An outstanding package of benefits to all passenger-carriers, in an advanced modern shape that marks it clearly as a vehicle for today and for the future.

Traditional strength and dependability combine with advanced design efficiency to make Transit's Bus

and Kombi models the ideal choice for "People Moving". The outstanding qualities of Transit offer benefits that are of particular importance to today's Bus and Kombi operator, and include:

- Comfort
- Safety and Driveability
- Low Cost of Operation

Comfort

- Optimum body width, combined with carefully designed seat configurations, provide a spacious environment for both driver and passengers.
- Independent front suspension (Short Wheelbase models), and 'I' beam suspension (Long Wheelbase models), give high standards of both ride and handling.
- Extensive use of modern sound-deadening materials to keep Transit's interior noise levels to car levels.

Safety and Driveability

- The Transit Driver sits behind the engine and front axle for maximum protection and ease of access.
- Transit has excellent visibility which is provided through the large windshield and side windows, and also by the high command driving position.

 The light precise steering and other controls give first class manoeuvrability.

Low Cost of Operation

- Fuel economy improved with latest design transmissions and engine refinements.
- Excellent access to engine compartment facilitates routine servicing.
- Fuel economy aided by aerodynamic body shape.


Contents

Transit — The People Mover	Page 2
The People-Moving Range	Page 3
9-seat Bus	Pages 4/5
Kombis	Pages 6/7
12 & 15-seat Kombi-Bus	Pages 8/9
First-Class Driver Environment	Pages 10/11
Low Cost of Operation	Page 12
Special Vehicles	Page 13
Colours and Trims	Page 14
Specifications	Page 15
Technical Data	Page 16



The People-Moving range






TRANSIT 9-SEAT GL BUS

9 seat GL Bus, with standard roof, and optional headlamp jetwash.

The luxuriously appointed Transit 9 seat GL Bus sets high standards of comfort for this size of passenger carrying vehicle. Its features include:

- High-back cloth trim seats with integral padded headrestraints fitted throughout.
- Driver's seat adjustable for: reach, height and fully variable rake, for maximum refinement of driving position.
- A dual front passenger seat fitted as standard, with an option of a single passenger seat; both types of seats have integral headrestraints.
- Superb visibility provided by the large windscreen, side and rear windows.
- Low interior noise levels through an extensive use of modern sound-deadening materials and developments to Transit's engines and transmissions.
- High quality floor carpet fitted throughout.

Dimensions (mm)



Weights (Kg) (standard roof)

Bus	Petrol	Diesel
	9 seats	9 seats
Standard engine L/kW	2.0/57	2.5/52
Kerbweight	1505	1655
Payload*	755	775
GVM	2260	2430


*Includes 75kg for driver

4

TRANSIT KOMBI

The Transit Kombi is a modern, efficient vehicle with outstanding qualities of versatility. Today's value-for-money model Kombi is ideally suited to a wide variety of passenger carrying uses, offering:

- 3 body styles: Short wheelbase with standard height roof.
 Short wheelbase with semi-high roof.
 Long wheelbase with standard height roof.
- Kombi models are also available without any rear seating for passenger carrying adaption by your Ford Dealer.
- A single front passenger seat can be fitted as an option to the standard dual front seat.
- Both the driver and dual front passenger seats can be fitted with optional headrestraints (standard models).
- Fully adjustable high-back cloth trimmed seat, with an integral headrestraint, is available as an option for the driver and front passengers (L models only).





Weight (Kg)

Kombis — 6.0m ³	Petrol	Diesel
Model	120	120
Standard Engine L/kW	2.0/57	2.5/52
Kerbweight	1331 (1341)	1491 (1501)
Payload*	1299 (1289)	1279 (1269)
GVM	2630	2770

Kombis - 6.6m3 data as shown in brackets

Kombis - 8.4m ³	Petrol	Diesel
Model	130	130
Standard Engine L/kW	2.0/57	2.5/52
Kerbweight	1519 (1581)	1671 (1733)
Payload*	1411 (1349)	1409 (1347)
GVM	2930	3080

Kombis - 10.0m3 data as shown in brackets

*Includes 75kg for driver



Main picture: Standard roof short wheelbase 6.0m³ Kombi with mud flaps front and rear, Letter should be should be


- Semi-high roof short wheelbase 6.6m³ Kombi with mud flaps front and rear, full wheelcovers
- 2. Long wheelbase 8.4m3 Kombi with mud flaps front and rear, full wheelcovers.

TRANSIT 12 & 15 SEAT KOMBI-BUS

To cater for the movement of groups of passengers Transit 12 and 15 seat Kombi-Bus models provide the ideal combination of comfort and efficiency, and offer the following benefits:

- A semi-high roof standard on 15 seat models (optional on 12 seat) giving an even more spacious interior through increased headroom.
- Entry to the rear passenger seats through either the sliding side load door or the large rear double hinged doors. A central gangway facilitates passenger entry and exit still further.
- On the standard model hard-wearing vinyl seat trim is fitted to all seats, with an option of both integral headrestraints and cloth seat trim.
- Cloth trimmed seats for the rear passengers can also be supplied as an option.
- As with the Transit 9 seat GL Bus, excellent visibility and low noise levels contribute to the interior environment of the 12 and 15 seat Kombi-Bus models.

Dimensions (mm)



Weights (Kg)

Kombi-Bus	Pet	trol	Diesel		
	12 Seats	15 Seats	12 Seats	15 Seats	
Standard Engine L/kW	2.0/57	2.0/57	2.5/52	2.5/52	
Kerbweight	1506	1720	1650	1866	
Payload *	974	1380	1000	1334	
GVM	2480	3100	2650	3200	

^{*} Includes 75kg for driver



Main picture: 12 seat Kombi-Bus Sub picture: 15 seat Kombi-Bus




The Transit driver enjoys a superb driving position, sitting well behind the front axle and engine within the wheelbase, providing excellent entry and exit with the added benefits of greater ride comfort and safety.

Driving position

The driver's seat has a fully variable, rake adjustment up to 22° (Fig. 1).

Instrumentation

Instruments are large and clear and, with the comprehensive warning lights, are mounted directly in front of the driver, complementing the outstanding driving position and visibility and contributing to Transit's excellent safety. (Fig. 3).



Visibility

The massive glass area offers first class visibility, with low sloping windshield and full drop door glass that compliments the excellent seating position. The resultant feeling of spaciousness within

the cab is very real, for this superb command position has been achieved without sacrificing other dimensions vital to driver comfort and productivity.





Ride and Handling

On short wheelbase Bus and Kombi models independent front suspension is featured - a hybrid Macpherson strut system. Also featured is rack and pinion steering gear and minimum scrub steering geometry, giving Transit low effort, positive steering with good feel and ex-cellent straight line and braking stability. This design of front suspension and steering combined with the latest design rear springs and shock absorbers give Transit outstanding ride and handling qualities.



Transit is comprehensively insulated, using a variety of specially selected and tested materials, to minimise noise intrusion for the driver and passengers.





Manoeuvrability Transit has low effort, precise steering providing a superior turning circle of 10.5m for the short wheelbase and 11.7m for the long wheelbase (kerb to kerb).

Power-Assisted Steering


Manoeuvrability can be improved still further on both long and short wheelbase models with the option of power assisted steering.



- Driver seat and dual passenger seat are high back design with integral head restraints ('GL' Buses, 'L' Kombis) — Fig. 1.
- Driver seat and dual passenger seat are standard height with 'A-frame' head restraints.
- Rear passenger seats are standard height with 'A-frame' head restraints ('L' 9-seat Buses), high back with integral head restraints ('GL' 9-Buses) and standard height with no head restraints (12 & 15 seat Kombi/Bus).
- · Single front passenger seat in lieu of dual passenger seat is available as an option (standard and 'L' models).




- Coil spring mounted inboard of the shock absorber unit to minimise interior intrusion
 Rack and Pinion Steering.
 Power Assisted Disc Brakes.
 Radial Ply Tyres.






11



Petrol Engines

- 1.6 litre OHC 46kW (63 PS)
- 2.0 litre OHC 57kW (77 PS)

Transit is available with two proven, reliable petrol engines giving a remarkable combination of lively performance and excellent fuel economy.



Direct Injection Diesel Engine

2.5 litre 52 kW (69 PS)

Recent Transit diesel engine improvements provide an increase in power, torque and fuel economy, plus a reduction in noise levels. These improvements have been possible through:

- Slim tip injectors which help the spread of injected fuel more effectively and burn more efficiently and as a result improving both combustion and reducing noise levels.
- A re-entrant bowl design combustion chamber which provides an improved degree of 'swirl' achieving the best balance of power, fuel economy and smoke levels.
- An improved piston ring pack design which improves emission and reduces oil consumption.

Matched Drivelines

Complementing the choice of engines there are two transmissions:

MT75-Manual

The MT75, 5 speed manual gearbox is designed to make full use of the engines dynamic qualities. It gives the driver smooth, slick gear changing (even reverse has synchromesh!).

A4LD—Automatic

Available as an option in Transit, the tried and tested 4-speed automatic transmission (A4LD) has been successfully installed in Ford car series. It offers the economy advantages of 4-speed automatic transmission.

TRANSIT VERSATILITY

tives, strong rugged construction and reputation for reliability make it the ideal basis for conversions.

but to facilitate the building of vehicles for specialist applications your Dealer can call upon the experience of Ford's Special Vehicle Operations (SVO). SVO aim to provide factory and specialist fitted options to meet individual customer requirements, where generally, the volumes would not justify the major investments for a regular production option.

Illustrated are just a few examples of the versatility of the conversions that are available on the

discussed with your local Ford Dealer.



Paint Colours

Operators can further enhance the appearance of their Bus or Kombi (and at the same time enhance their company's image) with a personalised livery. The large clear areas on the hood, side, and rear of the Transit's modern bodyshape are ideal for signwriting schemes.

Corrosion protection

The bodyshell undergoes an extensive extremely thorough preparation and painting process before reaching the final assembly line. (See illustration). Internal cavities are injected with a special wax, and the whole underbody, including wheelarches, is treated with PVC to complete Transit's corrosion protection process.

- A Top Coat
 B Primer
 C Cathodic Electrocoat Primer
 D Zinc Phosphate
 E Steel









Cardinal Red



Saffron Yellow









Light Blue

Guernsey Fabric in Shadow Grey Shadow Grey Delta Grain Vinyl





Interior Fed	tures - All Models		
Ashtray:	front an fascia rear side panels (Bus model only)		drivers; adjustable for reach and rake (Kombi models) adjustable for reach/rake and height (L. model Bus)
Controls:	three steering column located stalks controlling; lights windshield wipe/wash turn indicators/horn		high-back with adjustable headrestraint (Bus model) passengers; front dual (Kombi models) front dual low back with headrestraints (L. model Bus) front dual high-back with adjustable headrestraints (GL Bus model
Door stowage b	ins: front		rear low back with headrestraints (L. madel Bus)
Glove box:			rear high-back with adjustable headrestraints (GL Bus model)
Grab handle:	front passenger side	Seat belts:	outer inertia reel, inner static rear passengers (Bus model) lap only
Heater:	recirculatory setting an diesel engined models 3 speed with blower switch face-level vents	Seat trim:	vinyl cloth (Bus model only)
Electrical:	fuse panel below instrument panel	Steering wheel:	two spoke with soft feel rim
Instruments:	speedometer/odometer	Sunvisor:	driver and passenger
Instruments: speedometer/odometer fuel and temperature gauges warning lights for: direction indicators main beam battery/charge brake failure oil pressure warning light	Trim:	full length cab mat (carpet on GL Bus model) rubber mats an front door foot wells insulated cab mat vinyl door trim on front doors front wheel arch covers consolide trim	
Lights:	cab caurtesy light, door operated load compartment light		handbrake gaiter rear door or tailgate trim
main bea battery/cl brake fai oil pressu Lights: cab courtesy light, door ope			coat hooks (2) load compartment trim board (vinyl covered on Bus model)

Exterior Fe	eatures - All Models		
Body:	Semi-high roof (LWB Kombi anly)	Lights:	halogen headlamps
Bumpers:	front; full width polypropelene rear; full width steel		nazara nasners rar fog light reversing lights side repeat flashers
Doors:	front — hinged cab doors rear — hwin 180° opening with interior pull and trim (RHD SWB	Locks:	high security including steering column
	and all LWB models) side — sliding RH with integral step with tread plate & trim tailgate — (Bus and LHD SWB Kombi models)	Mirrors:	driver and passenger side
Fuel tank:	locking fuel filler cap 68 litres capacity	Mudflaps:	front rear (Bus model only)
Glass:	laminated windshield	Towing eyes:	front and rear
cab door drop windows bodyside windows (LHS) bodyside windows (LHS) heated rear windows (BHS)	Windshield wipe Tailgate wash/wi	rs; two speed with electric wash pe: (Bus model)	

	RHD		HD		RHD		HD
	Kombi	Bus	Kombi		Kombi	Bus	Komb
Mechanical				Interior			
Heavy duty battery	0	0	0	Single passenger seat	0	0	0
Limited slip differential	-	0	0	Headrestraint drivers and			
Trailer coupling pack	_	0	0	passengers seat	0	S	0
Power assisted steering	0	0	0	High-back seats (optional with L Bus)	0	S	0
Cold climate start pack (diesel engine only)	0	s	0	Rear seats 3 rows (SWB Kombi) 4 rows (LWB Kombi)	00	S	00
Headlamp jet wash		0		Rear seat fixings (standard with rear seats or optional rear mat)	0	s	0
Exterior				Vinyl seat trim (L pack only)	0	-	0
High centre gravity pack	0	_	0	Cloth seat trim (Standard models only)	0	S	0
Rear mud flaps	0	S	0	Rear seat belts	0	S	0
Sliding side load door/step (LHS)	S	_	_	Rear compartment mat	0	S	0
(RHS)	_	S	S	Rear compartment headlining and light	0	S	0
Semi-high roof version				Full bulkhead (not with rear seats)	0	-	0
(SWB models only)	0	0	0	Half bulkhead (not with rear seats)	0	_	0
Hinged rear doors (SWB models only)	S	0	0	Radio pre-equipment pack	0	0	0
Tailgate (RHD SWB only)	0	S	S	Radio (with L pack only)	0	0	0
Rear step	0	_	0	Tachograph	0	0	0
Sliding bodyside glass 1st light 2nd light (SWB only)	0	S S	00	O = Optional SWB = Shart w	heelbase		
Heated rear windows	0	0	0	5 5 1 1	16		
Tailgate wash/wipe (only with tailgate and optional with L Bus)	0	S	0	S = Standard LWB = Long wh	eelbase		

TECHNICAL DATA

General S	pecifications	3/9/12 seat 100/120	3/15 seat 130
Wheelbase(mm)	2815	S	_
	3020	-	S
Engine	1.6 Petrol (not with GL bus)	S	_
	2.0 Petrol (std with GL bus)	0	S
	2.5 Diesel	0	0
Clutch	240mm	S	S
Transmission	5 speed fully synchronised floor s	shift S	S
	Ford A4LD Automatic (only with		
	2.0l petrol engine)	0	0
Rear Axle	3.91, 4.11, 4.56 P	lease check availabili	ty by model
Ratios:1	4.63, 5.14, 5.83	vith your Ford Dealer.	
Brakes	Servo assisted disc/drum	S	S
Tyres	185 SR 14	-	S
	195 R 14 6PR Please check optional availability	S with your Ford Deale	er –

		3/9/12 seat 100/120	3/15 seat 130
Steering	Rack & Pinion	S	
	Recirculating Ball Power Assistance	0	S
Turning circle (m)	Kerb to Kerb 2815 w.b. 10.5	S	_
	3020 w.b. 11.7	_	S
	Wall to Wall 2815 w.b. 11.2	S	_
	3020 w.b. 12.4	***	S
Fuel Tank	68 litres	S	S
Electrical	Alternator 55 amp	S	S
System	Battery (CCA)		
	With 1.61 & 2.01 petrol 360	S .	S
	500	0	0
	With 2.5l diesel 500	S	S
	680	S O S O	s 0 s
	2 × 520		0

minimum period of 30 seconds with the terminal voltage not dropping below 7.20 volts.

Diesel Cold Start Equipment

520CCA or 680CCA + Thermostart or 2×520 CCA + Thermostart dependent on market.

Engine Specifications	2.5 litre Diesel	1.6 litre Petrol (LHD only)	2.0 litre Petrol
Capacity cc	2496	1593	1993
Bore x Stroke mm	93.67 x 90.54	87.6 × 66.0	90.8×77.0
Max. power kW (PS) at rpm	52(69) at 4000	46 (63) at 4750	57 (77) at 4500
Max torque Nm (mkg) at rpm	146 (15.0) at 2500	113 (11-2) of 3200	146 (15.0) at 2800
Compression ratio	19.1:1	8.1:1	8.1:1

'L' and 'GL' Pack Features

Feature	'L' Pack	GL**	
Wheel Covers	S	S	
Rear Recovery Eye	S	S	
Mudflaps — front — rear	S	SS	
Intermittent windscreen wipe	S	S	
Tailgate wash/wipe	0	S	
Heated rear windows	0	S	
Driver's seat: adjustable for:— reach rake height	S	S	
Single Passenger seat	0	0.	
Dual Passenger seat	S	S	
High Back seats: — front — rear	0	S	
Seat trimmed with shadow grey delta grain vinyl	0	_	
Seat trimmed with Guernsey fabric n shadow grey	s	S	
Soft Feel Steering wheel	S	S	
Clock & Trip Recorder	S	S	
Cigar Lighter	S	S	
Handbrake Gaiter	S	S	
Rear view mirror — dipping	S	S	
Door stowage bins	S	S	
Passenger grab handle (above door)	S	S	
Rubber floor mats	S	0	
Carpet	-	S	
Insulated cab mat and full NVH pack — petrol	S	S	
Radio	0	0	

Rubber mats are fitted in place of corpets when single seat is ordered.

Your Ford Dealer:

Ford policy is one of continuous improvement. The right to change prices, specifications or equipment at any time without notice is reserved. This is a General Export catalogue. Illustrations do not necessarily depict vehicle specifications available in every market or the standard equipment level. All data given in this catalogue is subject to production variations. Dimensions and weights are approximate only and will vary according to model, whether the vehicle is laden or unladen, payload, options fitted, etc. For exact information about any particular model please consult your Ford Dealer.

[&]quot;The GL pack is available only on the short wheelbase 9-seat bus.